



An autonomous low lift AMR with counterbalance and a lifting height of up to 6 metres. Its high degree of modularity and scalability makes it suitable for use in various production or warehouse premises.

**FORKLIFT AMR** 

The 1500FCB is ideal for repetitive flows and enables the quick and safe transport of pallets.



## **SPECIFICATION**

Туре	Low lift with counterbalance
Navigation	Contour/laser
Direction of drive	Forward/backward
Minimal turning radius	Depending on the pallet
Speed (m/s)	Forward: 2.0/backward: 0.5
Load capacity (kg)	1,500
Lift	Hydraulic
Lift (mm)	4,000/6,000
Dimensions (L, W, H in mm)	3,645x1,220x3,254
Forks	Forged
Max. pallet size (L, W, H in mm)	Length 1,500
Manipulation	Via static part/from the ground
Batteries	Li-FePO4
Charging	Inductive/automatic
Control	Manual control, touchscreen, steering handle
Safety scanners	Safety PLC, safety laser

Asseco CEIT AMRs are available with their **own MCS fleet manager with VDA 5050 standard** for guiding and monitoring logistics equipment in real time.

We offer a comprehensive **automatic logistics system**, **including AMR equipment**, **our own fleet manager and peripherals**.



asseco-ceit.com

E-mail: sales@asseco-ceit.com